



RCA-26 AMPLIFIER A-C FILAMENT

26

Filament	Coated	
Voltage	1.5	a-c or d-c volts
Current	1.05	amp.
Direct Interelectrode Capacitances:		
Grid to Plate	8.1	μmf
Grid to Filament	2.8	μmf
Plate to Filament	2.5	μmf
Maximum Overall Length		4-11/16"
Maximum Diameter		1-13/16"
Bulb	(2) (3)	ST-14
Base		Medium 4-Pin
Pin 1-Filament	(1) (4)	Pin 3-Grid
Pin 2-Plate		Pin 4-Filament


BOTTOM VIEW

AMPLIFIER (Class A)

Operating Conditions and Characteristics:

Filament	1.5	1.5	1.5	a-c volts
Plate	90	135	180 max.	volts
Grid*	-7	-10	-14.5	volts
Amp. Fact.	8.3	8.3	8.3	
Plate Res.	8900	7600	7300	ohms
Mut. Cond.	935	1100	1150	μmhos
Plate Cur.	2.9	5.5	6.2	ma.

* Grid volts measured from mid-point of a-c operated filament.



JULY 1, 1935


RCA RADIODOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

DATA


26

Cunningham
Radiotron
RCA-26

AVERAGE PLATE CHARACTERISTICS



AVERAGE CHARACTERISTICS



JULY 16, 1935

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-4428